



Advanced Technology. Quality Products. Responsive Service.

USA:
160 Ridgeland Dr., Suite 300
Greenville, SC 29601
Plant: 200 Tanner Dr.
Taylors, SC 29687
(864) 908-6057

Honduras:
Building #20, Zip Bufalo
Villanueva, Honduras
Office: 504-2574-9083
Email: excel-products@juno.com

EXTRALEV AL

REACTIVE/ DISPERSE DYE LEVELER & LUBRICANT

EXTRALEV AL is an anionic, jet dye leveling agent and lubricant. It has excellent wetting and penetrating properties and acts as a dispersant and leveling agent for reactive and disperse dyes. It greatly improves the levelness of hard to dye turquoise and other reactive dyes. It acts as a fiber to fiber and fiber to metal lubricant preventing rope marks, abrasion and tangles during preparation and dyeing.

GENERAL PROPERTIES:

Appearance:	Amber liquid
Ionic Nature:	Anionic
pH:	Approx. 7.0
Solubility:	Instant in water

ADVANTAGES:

1. Excellent leveling agent for hard to dye turquoise and other reactive dyes.
2. Wetting, penetrating, scouring for cotton and poly/cotton goods.
3. Dyebath lubricant without need for other lubricants.
4. Simplifies formulas and inventory by use of combination leveler/ lubricant.

METHOD OF APPLICATION:

Jet Dyeing: 1- 2% owg (on weight of goods) is recommended as a good starting point in preparation and dyeing, depending on desired properties- wetting, scouring, leveling, dye dispersing and leveling.

All data discussed herein are believed to be correct. However, this should not be accepted as a guarantee of their accuracy and confirming tests should be run in your own plant or laboratory. No statement should be construed as a recommendation for any use which would violate any patent right. Nothing contained herein shall constitute a guarantee or warranty with respect to the products described or their use.