



Advanced Technology. Quality Products. Responsive Service.

USA:
160 Ridgeland Dr., Suite 300
Greenville, SC 29601
Plant: 200 Tanner Dr.
Taylors, SC 29687
(864) 908-6057

Honduras:
Building #20, Zip Bufalo
Villanueva, Honduras
Office: 504-2574-9083
Email: excel-products@juno.com

EXTRALUBE 100

Dyebath Lubricant

EXTRALUBE 100 is a nonionic jet dye and beck lubricant. It is recommended to improve fiber to metal lubricity of cotton, polyester/cotton and synthetic fabric and yarns during wet processing. It does not interfere with dyeing. Being nonionic, it is very compatible with other dyeing auxiliaries.

GENERAL PROPERTIES:

Appearance:	Clear liquid
Ionic Nature:	Nonionic
pH:	Approx. 6.5 - 7.5
Solubility:	Dispersible in water

FEATURES:

1. Excellent fiber to metal lubricating properties.
2. Will not interfere with dyeing processes.
3. Compatible with dyes and other dyeing auxiliaries.
4. Economical and effective at low use levels.

METHOD OF APPLICATION:

Jet/Beck: 0.5-1 gm/l Extralube 100 is recommended, depending on the harshness of fibers and load amount.

All data discussed herein are believed to be correct. However, this should not be accepted as a guarantee of their accuracy and confirming tests should be run in your own plant or laboratory. No statement should be construed as a recommendation for any use which would violate any patent right. Nothing contained herein shall constitute a guarantee or warranty with respect to the products described or their use.