



Advanced Technology. Quality Products. Responsive Service.

USA:
160 Ridgeland Dr., Suite 300
Greenville, SC 29601
Plant: 200 Tanner Dr.
Taylors, SC 29687
(864) 908-6057

Honduras:
Building #20, Zip Bufalo
Villanueva, Honduras
Office: 504-2574-9083
Email: excel-products@juno.com

EXTRASOFT NP-25

Polyethylene Softener Emulsion

EXTRASOFT NP-25 is a high density, nonionic polyolefin softener and lubricant for plain and resin finishing of cotton and blend fabrics. It imparts a smooth, slick hand and improves sewability, tear, and tensile strength of finished goods. It is recommended for flame retardant finishes because of its extremely high melt point.

GENERAL PROPERTIES:

Appearance: Translucent liquid

Ionic Nature: Nonionic

pH: Approx. 8.0 - 9.0

Solubility: Instant in water

FEATURES:

1. Imparts soft surface hand and enhances effectiveness of other softeners.
2. Improves abrasion resistance, tear strength, and crease recovery angle.
3. Excellent for needle cutting and improved sewability properties.
4. Will not yellow or scorch during curing or hot pressing.
5. Recommended for flame retardant finishes. High melt point.

METHOD OF APPLICATION:

Resin and Plain Padding: 1 - 3 % owb

Napping or Sanding: 1 - 3 % owb

All data discussed herein are believed to be correct. However, this should not be accepted as a guarantee of their accuracy and confirming tests should be run in your own plant or laboratory. No statement should be construed as a recommendation for any use which would violate any patent right. Nothing contained herein shall constitute a guarantee or warranty with respect to the products described or their use.